

CLAIMS:

1. A method for applying a gain characteristic to an audio signal comprising the steps of:
- 5 storing data representing a plurality of gain characteristic at a plurality of different levels;
- repeatedly assessing the amplitude of an input signal;
- determining a gain characteristic to be applied to the input signal; and
- applying the thus determined gain characteristic to the input signal.
- 10 2. A method according to claim 1 in which the amplitude falls between two gain characteristics and an interpolation between these is made to apply to the input signal.
- 15 3. A method according to claim 1 or 2 including the step of storing at least one impulse response and applying a stored impulse response to the input signal in addition to the gain characteristic.
- SUB  
22 4. A method according to any preceding claim in which the gain  
20 characteristic to be applied to an input signal is determined in response to a manual input.
5. A method according to claim 3 or 4 in which an interpolation between two or more impulse responses is made and applied to the input signal.
- 25 6. A method according to claim 4 in which a manual input is used to select the impulse responses to be applied.
- SUB  
23 7. A method according to any preceding claim in which the gain  
30 characteristic corresponds to a gain characteristic of an audio signal processor.

8. Apparatus for applying a gain characteristic to an audio signal comprising:  
means for storing data representing a plurality of gain characteristics at a plurality of different levels;  
5 repeatedly assessing the amplitude of an input signal;  
determining a gain characteristic to be applied to the input signal; and  
applying the thus determined gain characteristic to the input signal.

9. Apparatus according to claim 8 in which the amplitude of the input  
10 signal falls between two gain characteristics and including means for interpolating between these two gain characteristics to produce a gain characteristic to be applied to the input signal.

10. A method according to claim 8 or 9 including means for storing at least  
15 one impulse response, and means for applying a stored impulse response to the input signal in addition to the gain characteristic.

84B  
24  
11. A method according to any of the claims 9 to 10 including a manual  
input for a gain characteristic to be applied to an input signal.

20  
12. Apparatus according to claim 10 or 11 including means for interpolating between two or more impulse responses before applying the interpolated response to the input signal.

25  
13. Apparatus according to claim 11 including a manual input to select the impulse response to be applied.

SUB  
25  
14. Apparatus according to any of claims 8 to 13 in which the gain characteristic corresponds to a gain characteristic of an audio signal processor.